

View Online at <https://aerobasegroup.com/nsn/5306-01-505-3631>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.6940 inches

Fastener Length:

Between 2.0540 inches and 2.0840 inches

Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

Width Between Flats:

Between 0.678 inches and 0.690 inches

Grip Diameter:

Between 0.4516 inches and 0.4526 inches

End Application:

C-135 stratolifter

Thread Diameter:

0.4375 inches

Grip Length:

Between 1.3650 inches and 1.3850 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 ty ii, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.