

View Online at <https://aerobasegroup.com/nsn/5306-01-505-5884>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.710 inches and 0.760 inches

**Fastener Length:**

Between 1.845 inches and 1.875 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.250 inches and 0.265 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Grip Diameter:**

Between 0.5141 inches and 0.5151 inches

**End Application:**

C-135 aircraft

**Thread Diameter:**

0.500 inches

**Grip Length:**

Between 1.115 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Bolt, hex head, close tolerance, alloy steel, long thread, sel

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.