NSN 5306-01-506-0088

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-506-0088 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.528 inches **Fastener Length:** 2.7155 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.5141 inches and 0.5151 inches **End Application:** C-135 stratolifter **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.1775 inches and 2.1975 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, hex head, short thread, self-locking and nonlocking Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard 1st material response or ams5732 assn standard 1st material response or ams5737 assn standard 1st material response or ams5853 assn standard 1st material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 ty ii, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5306-01-506-0088

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0