NSN 5306-01-506-0548

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-506-0548 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.184 inches **Fastener Length:** Between 4.4950 inches and 4.4980 inches **Head Style:** Dished hexagon **Head Height:** Between 0.438 inches and 0.453 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Grip Diameter:** Between 0.8690 inches and 0.8695 inches **End Application:** C-135 stratolifter **Thread Diameter:** 0.875 inches **Grip Length:** Between 3.3025 inches and 3.3225 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, hex head, close tolerance Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 ty ii, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5306-01-506-0548

Shear Bolt - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.