## NSN 5306-01-506-0552

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-506-0552

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
1.184 inches	
Fastener Length:	
Between 4.4950 inches and	4.4980 inches
Head Style:	
Dished hexagon	
Head Height:	
Between 0.438 inches and 0	.453 inches
Width Between Flats:	
Between 1.239 inches and 1	.252 inches
Grip Diameter:	
Between 0.9042 inches and	0.9052 inches
End Application:	
C-135 stratolifter	
Thread Diameter:	
0.875 inches	
Grip Length:	
Between 3.3025 inches and	3.3225 inches
Thready Qty Per Inch (tpi):	
14	
Min. Tensile Strength (psi)	
160000 pounds per square i	nch
Product Name:	
Bolt, hex head, close toleran	ce
Material:	
Steel comp e4340 or steel c	omp 8740
Material Specification:	
Mil-s-6049 military specificat	ion 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd
material response or ams64	15 assn standard 2nd material response
Surface Treatment:	
Cadmium	
Surface Treatment Specific	cation:
Qq-p-416 ty ii, cl 2 federal s	pecification all treatment responses
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5306-01-506-0552

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.

