

View Online at <https://aerobasegroup.com/nsn/5306-01-506-4909>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.480 inches

**Fastener Length:**

Between 1.465 inches and 1.495 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.338 inches and 0.358 inches

**Width Between Flats:**

0.419 inches

**Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

**Extended Washer Thickness:**

Between 0.072 inches and 0.092 inches

**Hole Diameter:**

Between 0.185 inches and 0.225 inches

**Grip Diameter:**

Between 0.311 inches and 0.312 inches

**End Application:**

Apache attck helicopter

**Thread Diameter:**

0.312 inches

**Grip Length:**

1.000 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Product Name:**

Bolt, tension, external wrenching, 220 ksi, 650 degrees f, ph13-8mo

**Material:**

Stainless steel

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0