
NSN 5306-01-507-2163

Shear Bolt - Page 1 of 2



AeroBase Group

Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 0.786 inches Fastener Length: Between 2.459 inches and 2.489 inches **Head Style:** Spline extended washer **Head Height:** 0.337 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** 0.054 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches Head Minor Diameter: Between 0.438 inches and 0.453 inches **End Application:** C17a aircraft **Thread Diameter:** 0.375 inches Grip Length: Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Minimum Yield Strength: 125000 pounds per square inch Surface Finish: 32.0 microinches grip **Product Name:** Bolt, tension-spline drive, inconel718, 220-255 ksi ftu Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment:** Passivate

NSN 5306-01-507-2163

Shear Bolt - Page 2 of 2



Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0