

View Online at <https://aerobasegroup.com/nsn/5306-01-507-7841>

Thread Class:

Aal

Thread Direction:

Right-hand

Thread Length:

1.184 inches

Fastener Length:

Between 5.044 inches and 5.074 inches

Head Style:

Dished hexagon

Head Height:

Between 0.438 inches and 0.453 inches

Width Between Flats:

Between 1.239 inches and 1.252 inches

Grip Diameter:

Between 0.8886 inches and 0.8896 inches

End Application:

C-135 aircraft

Thread Diameter:

0.875 inches

Grip Length:

Between 3.865 inches and 3.885 inches

Thread Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

160000 pounds per square inch

Product Name:

Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread diameter locking and non-locking, 160 ksi ftu

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 ty ii, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.