

View Online at <https://aerobasegroup.com/nsn/5306-01-507-7841>

**Thread Class:**

Aal

**Thread Direction:**

Right-hand

**Thread Length:**

1.184 inches

**Fastener Length:**

Between 5.044 inches and 5.074 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.438 inches and 0.453 inches

**Width Between Flats:**

Between 1.239 inches and 1.252 inches

**Grip Diameter:**

Between 0.8886 inches and 0.8896 inches

**End Application:**

C-135 aircraft

**Thread Diameter:**

0.875 inches

**Grip Length:**

Between 3.865 inches and 3.885 inches

**Thread Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Product Name:**

Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread diameter locking and non-locking, 160 ksi ftu

**Material:**

Steel comp e4340 or steel comp 8740

**Material Specification:**

Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 ty ii, cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.