## NSN 5306-01-508-6789

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-508-6789 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.360 inches **Fastener Length:** 3.672 inches **Head Style:** Hexagon **Head Height:** 0.156 inches Width Between Flats: Between 0.490 inches and 0.502 inches **Grip Diameter:** 0.311 inches **Thread Diameter:** 0.312 inches **Grip Length:** 3.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8735 or steel comp 6150 **Material Specification:** Ams6322 assn standard 1st material response or mil-s-6049 military specification 1st material response or ams6382 assn standard 2nd material response or ams6415 assn standard 3rd material response or mil-s-5000 military specification 4th material response or mil-s-6098 military specification 5th material response or mil-s-8503 military specification all material responses **Surface Treatment:** Cadmium head **Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response head **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:** 

## NSN 5306-01-508-6789

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.