NSN 5306-01-508-7186



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-508-7186 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.344 inches **Fastener Length:** 2.344 inches **Head Style:** Hexagon **Head Height:** 0.094 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Grip Diameter:** Between 0.189 inches and 0.190 inches **Thread Diameter:** 0.190 inches **Grip Length:** 2.000 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 8740 or steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8735 or steel comp 6150 **Material Specification:** Ams6322 assn standard 1st material response or mil-s-6049 military specification 1st material response or ams6382 assn standard 2nd material response or ams6415 assn standard 3rd material response or mil-s-5000 military specification 4th material response or mil-s-6098 military specification 5th material response or mil-s-8503 military specification all material responses **Surface Treatment:** Cadmium grip **Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response grip **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5306-01-508-7186

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.