## NSN 5306-01-509-2005

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-509-2005

Thread Class:
3a

Thread Direction:
Right-hand
Thread Length:
0.813 inches

Between 2.207 inches and 2.237 inches

Head Style:

**Fastener Length:** 

Spline extended washer

**Head Height:** 

Between 0.420 inches and 0.440 inches

**Extended Washer Diameter:** 

Between 0.637 inches and 0.651 inches

**Extended Washer Thickness:** 

Between 0.113 inches and 0.133 inches

**Grip Diameter:** 

Between 0.5135 inches and 0.5141 inches

**Head Minor Diameter:** 

Between 0.637 inches and 0.651 inches

**End Application:** 

B-52 aircraft

**Thread Diameter:** 

0.500 inches

**Grip Length:** 

Between 1.302 inches and 1.322 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

**Product Name:** 

Bolt, 12 point head, 220 ksi min trnsile 125 min shear, nickel alloy 718 (.0156 oversize)

Material:

Nickel alloy 718

**Surface Treatment:** 

Cadmium and chromate

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5306-01-509-2005

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0