NSN 5306-01-509-3782

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-509-3782

Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.663 inches Fastener Length: 4.538 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches Shank Unthreaded Hole Diameter:						
Thread Direction: Right-hand Thread Length: 0.663 inches Fastener Length: 4.538 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Right-hand Thread Length: 0.663 inches Fastener Length: 4.538 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Thread Length: 0.663 inches Fastener Length: 4.538 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
0.663 inches Fastener Length: 4.538 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Fastener Length: 4.538 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
4.538 inches Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Head Style: Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Hexagon Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Head Height: Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches						
Width Between Flats: Between 0.554 inches and 0.564 inches						
Between 0.554 inches and 0.564 inches						
Shank Unthreaded Hole Diameter						
Shank Unthreaded Hole Diameter:						
0.106 inches first hole and 0.116 inches first hole						
Thread Diameter:						
0.375 inches						
Grip Length:						
Between 3.860 inches and 3.890 inches						
Features Provided:						
Finished head						
Thready Qty Per Inch (tpi):						
24						
Min. Tensile Strength (psi):						
140000 pounds per square inch						
Distance From Head Largest Bearing Surface To Shank Hole Center:						
4.298 inches first hole and 4.328 inches first hole						
Product Name:						
Navy special project						
Material:						
Iron alloy 660						
Material Specification:						
Ams5371 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Qq-p-35 federal specification single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						
•						

80205-nas1006 professional/industrial association standard

NSN 5306-01-509-3782

Machine Bolt - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0