NSN 5306-01-510-5643

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-510-5643

3a
Thread Direction:
Right-hand
Thread Length:
0.545 inches
Fastener Length:
Between 1.705 inches and 1.735 inches
Head Style:
Spline extended washer
Head Height:
0.393 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
0.063 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Head Minor Diameter:
Between 0.673 inches and 0.688 inches
End Application:
C-17a aircraft
Thread Diameter:
0.437 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
180000 pounds per square inch
Surface Finish:
32.0 microinches grip
Product Name:
Bolt, tension-spline drive, incinnel 718, 180-220 ksi ftu
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5306-01-510-5643

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0