NSN 5306-01-511-8374

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-511-8374

g
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 1.098 inches and 1.128 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Grip Diameter:
Between 0.264 inches and 0.265 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
End Application:
C-130 aircraft
Thread Diameter:
0.250 inches
Grip Length:
Between 0.678 inches and 0.698 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740
Surface Treatment:
Cadmium or chromate
Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

80205-nas6604 professional/industrial association standard

NSN 5306-01-511-8374

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0