

View Online at <https://aerobasegroup.com/nsn/5306-01-512-6695>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.670 inches and 0.680 inches

**Fastener Length:**

Between 2.580 inches and 2.620 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.234 inches and 0.266 inches

**Width Between Flats:**

Between 0.615 inches and 0.627 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**End Application:**

2815-00-124-5387

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.406 inches first hole and 2.437 inches first hole

**Material:**

Steel comp 4140 or steel comp 8630 or steel comp 8740

**Material Specification:**

Qq-s-624 federal specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0