NSN 5306-01-512-9318

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-512-9318

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.455 inches and 0.505 inches
Fastener Length:
Between 1.090 inches and 1.120 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.338 inches and 0.358 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
0.082 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Surface Finish:
32.0 microinches bearing surface of head
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium or cadmium and chromate
Surface Treatment Specification:
Bnas 672 military specification all treatment responses or mil-c8837 type 2 class 2 military specification 2nd treatment response

NSN 5306-01-512-9318

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

spec.