

View Online at <https://aerobasegroup.com/nsn/5306-01-513-1075>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.464 inches

Fastener Length:

Between 1.193 inches and 1.243 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.290 inches and 0.310 inches

Width Between Flats:

0.347 inches

Extended Washer Diameter:

Between 0.428 inches and 0.438 inches

Extended Washer Thickness:

Between 0.059 inches and 0.079 inches

Grip Diameter:

0.249 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.081 inches first hole

End Application:

E-2c, hawkeye, aircraft

Thread Diameter:

0.250 inches

Grip Length:

Between 0.740 inches and 0.760 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

8540 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.087 inches first hole

Material:

Stainless steel

Material Specification:

Sae-ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0