## NSN 5306-01-513-1075

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-513-1075

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.464 inches
Fastener Length:
Between 1.193 inches and 1.243 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.290 inches and 0.310 inches
Width Between Flats:
0.347 inches
Extended Washer Diameter:
Between 0.428 inches and 0.438 inches
Extended Washer Thickness:
Between 0.059 inches and 0.079 inches
Grip Diameter:
0.249 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.081 inches first hole
End Application:
E-2c, hawkeye, aircraft
Thread Diameter:
0.250 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
8540 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.087 inches first hole
Material:
Stainless steel
Material Specification:
Sae-ams5629 assn standard single material response
Surface Treatment:
Passivate

**Surface Treatment Specification:** 

barrace freatment opecinication.

Qq-p-35 federal specification single treatment response

## NSN 5306-01-513-1075

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0