

NSN 5306-01-513-1091 Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-513-1091 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.929 inches **Fastener Length:** Between 3.869 inches and 3.899 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.701 inches and 0.721 inches Width Between Flats: Between 0.803 inches and 0.814 inches **Extended Washer Diameter:** Between 1.220 inches and 1.230 inches **Extended Washer Thickness:** 0.178 inches **Grip Diameter:** Between 0.748 inches and 0.749 inches **End Application:** E-2c, hawkeye, aircraft **Thread Diameter:** 0.750 inches **Grip Length:** Between 2.865 inches and 2.885 inches Thready Qty Per Inch (tpi): 16

Min. Tensile Strength (psi):

220000 pounds per square inch

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-513-1091

Shear Bolt - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0