## NSN 5306-01-513-3998

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-513-3998

View Online at https://aerobasegroup.com/nsn/5306-01-513-3998
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.640 inches and 0.690 inches
Fastener Length:
Between 1.900 inches and 1.930 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.425 inches and 0.445 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Extended Washer Diameter:
Between 0.740 inches and 0.750 inches
Extended Washer Thickness:
Between 0.089 inches and 0.109 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Thread Diameter:
0.438 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Cadmium  Surface Transfer of Cassifications
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:

Unjf

## NSN 5306-01-513-3998

Shear Bolt - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0