NSN 5306-01-513-4214

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-513-4214
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.535 inches and 0.585 inches
Fastener Length:
Between 1.982 inches and 2.012 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.378 inches and 0.398 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
Between 0.081 inches and 0.101 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.427 inches and 1.447 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837 type 2, cl 2 military specification single treatment response or qq-p-416 type 2, cl 2 federal specification single treatment
response

Thread Series Designator:

Unjf

NSN 5306-01-513-4214

Shear Bolt - Page 2 of 2



NI/a
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

Shelf Life: