## NSN 5306-01-513-4586

Shear Bolt - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5306-01-513-4586

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.736 inches and 0.786 inches
Fastener Length:
Between 1.808 inches and 1.838 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.494 inches and 0.514 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Extended Washer Diameter:
Between 0.818 inches and 0.828 inches
Extended Washer Thickness:
Between 0.113 inches and 0.133 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 1.052 inches and 1.072 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp h11
Surface Treatment:
Cadmium
Thread Series Designator:
Unjf
Specification Data:
26512-gb511 professional/industrial association standard
Shelf Life:
N/a

## NSN 5306-01-513-4586

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0