NSN 5306-01-513-4760

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-513-4760 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.428 inches and 0.448 inches **Fastener Length:** Between 1.485 inches and 1.515 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **End Application:** Rq-4a **Thread Diameter:** 0.313 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 11100 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.318 inches first hole **Product Name:** Bolt, shear Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5306-01-513-4760 Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

Demilitarization:

No

Fiig:

A003b0