NSN 5306-01-513-4812



Shear Bolt - Page 1 of 2	Gro
View Online at https://aerobasegroup.com/nsn/5306-01-513-4812	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.736 inches and 0.786 inches	
Fastener Length:	
Between 1.371 inches and 1.401 inches	
Head Style:	
Double hexagon w/hole	
Head Height:	
Between 0.494 inches and 0.514 inches	
Width Between Flats:	
Between 0.553 inches and 0.564 inches	
Extended Washer Diameter:	
Between 0.818 inches and 0.828 inches	
Extended Washer Thickness:	
Between 0.113 inches and 0.133 inches	
Grip Diameter:	
Between 0.4985 inches and 0.4995 inches	
Thread Diameter:	
0.500 inches	
Grip Length:	
Between 0.615 inches and 0.635 inches	
Thready Qty Per Inch (tpi):	
20	
Min. Tensile Strength (psi):	
220000 pounds per square inch	
Hardness Rating:	
46.0 rockwell c and 50.0 rockwell c	
Product Name:	
Navy special project	
Special Features:	
Ceramic bonded	

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Sps-p-671, cagec 56878 mfr ref single treatment response

NSN 5306-01-513-4812

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0