## NSN 5306-01-513-4895

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-513-4895 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.585 inches and 0.665 inches **Fastener Length:** Between 1.423 inches and 1.453 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.464 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Extended Washer Diameter:** Between 0.820 inches and 0.830 inches **Extended Washer Thickness:** 0.083 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Thread Diameter:** 0.438 inches **Grip Length:** Between 0.788 inches and 0.838 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5306-01-513-4895

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0