NSN 5306-01-513-4942

Shear Bolt - Page 1 of 2

Thread Class:

3a

View Online at https://aerobasegroup.com/nsn/5306-01-513-4942



Thread Direction: Right-hand Thread Length: Between 0.535 inches and 0.585 inches Fastener Length: Between 0.857 inches and 0.887 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.378 inches and 0.398 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** Between 0.081 inches and 0.101 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Product Name:** Navy special project **Special Features:** Ceramic bonded Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response Surface Treatment: Aluminum **Surface Treatment Specification:** Sps-p-671, cagec 56878 mfr ref single treatment response

NSN 5306-01-513-4942

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

