

View Online at <https://aerobasegroup.com/nsn/5306-01-513-4995>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.803 inches and 0.853 inches

Fastener Length:

Between 5.688 inches and 5.718 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.547 inches and 0.567 inches

Width Between Flats:

Between 0.616 inches and 0.627 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.123 inches and 0.143 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Thread Diameter:

0.562 inches

Grip Length:

Between 4.865 inches and 4.885 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.488 inches first hole and 5.518 inches first hole

Product Name:

Navy special project

Material:

Steel comp h11

Surface Treatment:

Cadmium

Thread Series Designator:

Unjf

Specification Data:

26512-gb511gf professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0