

View Online at <https://aerobasegroup.com/nsn/5306-01-514-3590>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.457 inches and 0.477 inches

**Fastener Length:**

1.092 inches

**Head Style:**

Spline drive shear head

**Head Height:**

0.187 inches

**Grip Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.081 inches first hole

**Head Minor Diameter:**

0.517 inches

**End Application:**

Wing aircraft

**Thread Diameter:**

0.312 inches

**Grip Length:**

0.625 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.968 inches first hole and 0.978 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Amsqq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0