NSN 5306-01-515-2224

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-515-2224 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.370 inches **Fastener Length:** Between 3.480 inches and 3.510 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** Between 3.115 inches and 3.135 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 6980 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 3.325 inches first hole Material: Steel **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-01-515-2224

Shear Bolt - Page 2 of 2



Fiig:

A003b0