

View Online at <https://aerobasegroup.com/nsn/5306-01-515-2224>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.370 inches

**Fastener Length:**

Between 3.480 inches and 3.510 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 3.115 inches and 3.135 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

6980 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.325 inches first hole

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0