

View Online at <https://aerobasegroup.com/nsn/5306-01-516-0948>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.740 inches and 0.860 inches

**Fastener Length:**

Between 6.140 inches and 6.187 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.109 inches and 0.141 inches

**Width Between Flats:**

Between 0.365 inches and 0.377 inches

**First Diameter From Head:**

Between 0.137 inches and 0.145 inches

**Second Diameter From Head:**

Between 0.137 inches and 0.145 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 5.280 inches and 5.447 inches

**End Application:**

F-16 a/c

**Thread Diameter:**

0.190 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Product Name:**

Bolt

**Material:**

Steel comp 431

**Material Specification:**

Mil-s-18732 military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-18732 spec.