## NSN 5306-01-516-6422

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-516-6422

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.598 inches
Fastener Length:
1.512 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.311 inches and 0.312 inches
Head Minor Diameter:
Between 0.360 inches and 0.375 inches
End Application:
F/a-22 raptor
Thread Diameter:
0.313 inches
Grip Length:
0.438 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Product Name:
Bolt, machine
Material:
Nickel alloy 718
Material Specification:
Ams5662j federal specification 1st material response and ams5663 assn standard 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5306-01-516-6422

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0