

View Online at <https://aerobasegroup.com/nsn/5306-01-517-0715>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.614 inches

**Fastener Length:**

2.176 inches

**Head Style:**

Spline extended washer

**Head Height:**

0.337 inches

**Extended Washer Diameter:**

0.696 inches

**Extended Washer Thickness:**

0.054 inches

**Grip Diameter:**

0.374 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Head Minor Diameter:**

0.438 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.562 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.963 inches first hole

**Product Name:**

Bolt-close tolerance, spline drive, flange head

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0