## NSN 5306-01-517-6568

Shear Bolt - Page 1 of 2



View Or	nline at https://aerobasegroup.com/nsn/5306-01-517-6568
Thread	Class:
3a	
Thread	Direction:
Right-ha	and
Thread	Length:
0.444 in	ches
Fastene	er Length:
2.031 in	ches
Head St	tyle:
Dished	hexagon
lead H	eight:
Betweer	n 0.156 inches and 0.171 inches
Vidth E	Between Flats:
Betweer	n 0.492 inches and 0.502 inches
Grip Dia	ameter:
3etweei	n 0.3110 inches and 0.3120 inches
Shank (	Unthreaded Hole Diameter:
).081 in	ches first hole
hread	Diameter:
.3125 i	nches
Grip Le	ngth:
.562 in	ches
hready	y Qty Per Inch (tpi):
4	
in. Te	nsile Strength (psi):
60000	pounds per square inch
Distanc	e From Head Largest Bearing Surface To Shank Hole Center:
.751 in	ches first hole
Special	Features:
N/drille	d shank bolt
Materia	l:
ron allo	y 660
Surface	Treatment:
Cadmiu	m and chromate
Thread	Series Designator:
Unjf	
Shelf Li	ife:
N/a	
Unit Of	Measure:
-	
Domilit	arization:
Deminia	

## NSN 5306-01-517-6568

Shear Bolt - Page 2 of 2

Fiig: A003b0

