

View Online at <https://aerobasegroup.com/nsn/5306-01-517-8378>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.669 inches and 0.719 inches

**Fastener Length:**

2.069 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.219 inches and 0.234 inches

**Width Between Flats:**

Between 0.678 inches and 0.690 inches

**Grip Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Unthreaded Hole Diameter:**

0.111 inches first hole

**Thread Diameter:**

0.438 inches

**Grip Length:**

Between 1.365 inches and 1.385 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.893 inches first hole and 2.243 inches first hole

**Surface Finish:**

32.0 microinches bearing surface of head

**Material:**

Iron alloy 660

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0