NSN 5306-01-518-1489

Close Tolerance Bolt - Page 1 of 1

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-518-1489

3a
Thread Direction:
Right-hand
Thread Length:
0.694 inches
Fastener Length:
2.256 inches
Head Style:
Dished hexagon
Head Height:
0.219 inches
Width Between Flats:
0.686 inches
Grip Diameter:
0.764 inches
Shank Unthreaded Hole Diameter:
0.440 inches
Thread Diameter:
0.4375 inches
Grip Length:
1.562 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 20
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi):
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator: Unjf
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator: Unjf Shelf Life:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator: Unjf Shelf Life: N/a
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator: Unjf Shelf Life: N/a
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 1600000 pounds per square inch Special Features: W/drilled shank Material: Iron alloy 660 Surface Treatment: Cadmium Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No