NSN 5306-01-518-9727



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-518-9727 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 3.182 inches and 3.212 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **End Application:** Rq-4a **Thread Diameter:** 0.190 inches **Grip Length:** Between 2.865 inches and 2.885 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads **Product Name:** Bolt, shear Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:**

N/a

Unjf

Shelf Life:

Thread Series Designator:

Qq-p-416 type 2 cl 2 federal specification all treatment responses

NSN 5306-01-518-9727

Shear Bolt - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.