NSN 5306-01-519-2347

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-519-2347 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.410 inches and 1.440 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches Single Shear Strength: 95000 pounds per square inch **End Application:** Boeing b757 aircraft **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Special Features:** Bolt is shot peened prior to chroium plating per sae-ams-s-13165; bolt is passivated after chromium plating Material: Iron alloy 660 **Material Specification:** Sae-ams5731 assn standard single material response or sae-ams5732 assn standard single material response or sae-ams5737 assn standard single material response or sae-ams5853 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Sae-ams-qq-p-35 assn standard single treatment response

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5306-01-519-2347

Shear Bolt - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A003b0