

View Online at <https://aerobasegroup.com/nsn/5306-01-519-7240>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.781 inches

**Fastener Length:**

Between 3.516 inches and 3.562 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.958 inches and 0.987 inches

**Head Height:**

Between 0.327 inches and 0.348 inches

**Locking Feature:**

Patch threads or pellet threads

**Internal Drive Style:**

Cross recess type 1

**End Application:**

Support of pre-provisioning items for which navicp phil acts as poe

**Thread Diameter:**

0.500 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

19810 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Minimum Yield Strength:**

29400 pounds per square inch

**Criticality Code Justification:**

Agav

**Product Name:**

Bolt, self-locking, 75 ksi, 125 ksi ftu, pan head, cross recessed

**Special Features:**

Internal drive in accordance w/ms9006

**Material:**

Steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or ams 6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 3 federal specification single treatment response

**Supplementary Features:**

Grip diameter at 0.4970/0.4995 inch diameter and grip length is at 2.740/2.760 inch

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.