NSN 5306-01-520-5058

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-520-5058

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.499 inches |
| Fastener Length: |
| Between 1.265 inches and 1.312 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.313 inches and 0.344 inches |
| Width Between Flats: |
| Between 0.679 inches and 0.689 inches |
| Hole Diameter: |
| Between 0.065 inches and 0.075 inches |
| Grip Diameter: |
| Between 0.433 inches and 0.437 inches |
| Thread Diameter: |
| 0.437 inches |
| Grip Length: |
| Between 0.734 inches and 0.766 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 20 |
| Hole Configuration Style: |
| Hexagon flats |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 3 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5306-01-520-5058

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0