NSN 5306-01-520-8719

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-520-8719

| Thread Class: | |
|--|--|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.643 inches | |
| Fastener Length: | |
| 1.9555 inches | |
| Head Style: | |
| Double hexagon w/hole | |
| Head Height: | |
| 0.340 inches | |
| Width Between Flats: | |
| Between 0.490 inches and 0.507 inches | |
| Extended Washer Diameter: | |
| Between 0.490 inches and 0.507 inches | |
| Extended Washer Thickness: | |
| 0.091 inches | |
| Hole Diameter: | |
| 0.260 inches | |
| Grip Diameter: | |
| Between 0.3735 inches and 0.3745 inches | |
| Thread Diameter: | |
| 0.375 inches | |
| Grip Length: | |
| 1.3125 inches | |
| Hole Quantity: | |
| 1 | |
| Ноје Туре: | |
| Drilled | |
| Thready Qty Per Inch (tpi): | |
| 24 | |
| Hole Configuration Style: | |
| Double hexagon longitudinal hole | |
| Color: | |
| Black threads | |
| Material: | |
| Nickel alloy 718 | |
| Material Specification: | |
| Ams5662 assn standard single material response or ams5962 assn standard single material response | |
| Surface Treatment: | |
| Aluminum | |

NSN 5306-01-520-8719

Close Tolerance Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

