

View Online at <https://aerobasegroup.com/nsn/5306-01-520-8957>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

0.9875 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.455 inches and 0.510 inches

**Locking Feature:**

Pellet locking feature

**Grip Diameter:**

Between 0.2481 inches and 0.2485 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.5625 inches

**Thready Qty Per Inch (tpi):**

28

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.6845 inches first hole

**Material:**

Stainless steel

**Material Specification:**

Ams5737 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0