NSN 5306-01-520-8988

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-520-8988 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.910 inches **Fastener Length:** Between 1.953 inches and 1.983 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.470 inches and 0.490 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.123 inches and 0.143 inches **Hole Diameter:** Between 0.050 inches and 0.060 inches **Grip Diameter:** 0.5615 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.958 inches and 1.978 inches **Hole Quantity:** Hole Type: Drilled

Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi):

...... renene en engan (per).

200000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Passivate

NSN 5306-01-520-8988

Close Tolerance Bolt - Page 2 of 2



	Surface	Treatment	Specification:
--	---------	------------------	----------------

Qq-p-35, class200fc12 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0