

View Online at <https://aerobasegroup.com/nsn/5306-01-520-8992>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.910 inches

**Fastener Length:**

Between 1.953 inches and 1.983 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.470 inches and 0.490 inches

**Width Between Flats:**

Between 0.616 inches and 0.627 inches

**Extended Washer Diameter:**

Between 0.928 inches and 0.938 inches

**Extended Washer Thickness:**

Between 0.123 inches and 0.143 inches

**Hole Diameter:**

Between 0.050 inches and 0.060 inches

**Grip Diameter:**

0.5615 inches

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 1.865 inches and 1.988 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

200000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, class200fc12 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0