

View Online at <https://aerobasegroup.com/nsn/5306-01-521-2034>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

0.885 inches

Head Style:

Dished hexagon

Head Height:

Between 0.110 inches and 0.125 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Hole Diameter:

Between 0.046 inches and 0.056 inches

Grip Diameter:

Between 0.188 inches and 0.189 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.080 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

0.562 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.721 inches first hole

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Ams 6415 assn standard 1st material response or ams 6322 assn standard 2nd material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6203 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.