

View Online at <https://aerobasegroup.com/nsn/5306-01-521-2933>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.370 inches

Fastener Length:

0.808 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.429 inches and 0.439 inches

Hole Diameter:

Between 0.048 inches and 0.058 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.248 inches and 0.249 inches

Thread Diameter:

0.250 inches

Grip Length:

0.438 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon corners

Material:

Steel comp 4340 bearing surface of head or steel comp 8740 bearing surface of head

Material Specification:

Mil-dtl-18240 military specification single material response locking feature

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6204 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.