NSN 5306-01-521-2934



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-521-2934 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.528 inches **Fastener Length:** 2.903 inches **Head Style:** Dished hexagon **Head Height:** Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.678 inches and 0.690 inches **Grip Diameter:** Between 0.436 inches and 0.437 inches **Thread Diameter:** 0.437 inches **Grip Length:** 2.375 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Ams 6415 assn standard 1st material response or ams 6322 assn standard 2nd material response or mil-c-6049 military specification 2nd material response **Surface Treatment:** Cadmium head **Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response head **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6207 professional/industrial association standard

Demilitarization: No

Unit Of Measure:

Shelf Life:

N/a

NSN 5306-01-521-2934

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-6049 spec.