## NSN 5306-01-521-2934

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-521-2934

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

Thread Length:

0.528 inches

## Fastener Length:

2.903 inches

#### Head Style:

Dished hexagon

Head Height:

Between 0.219 inches and 0.234 inches

## Width Between Flats:

Between 0.678 inches and 0.690 inches

#### Grip Diameter:

Between 0.436 inches and 0.437 inches

**Thread Diameter:** 

0.437 inches

## Grip Length:

2.375 inches

Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4340 or steel comp 8740

## **Material Specification:**

Ams 6415 assn standard 1st material response or ams 6322 assn standard 2nd material response or mil-c-6049 military specification 2nd material response

#### Surface Treatment:

Cadmium head

## **Surface Treatment Specification:**

Qq-p-416, tyii, cl2 federal specification single treatment response head

## Thread Series Designator:

Unjf

#### Specification Data:

80205-nas6207 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

No

# NSN 5306-01-521-2934

Shear Bolt - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-c-6049 spec.

