

View Online at <https://aerobasegroup.com/nsn/5306-01-521-9209>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.036 inches and 1.076 inches

**Fastener Length:**

Between 1.036 inches and 1.076 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.701 inches and 0.721 inches

**Width Between Flats:**

0.8125 inches

**Extended Washer Diameter:**

Between 1.220 inches and 1.230 inches

**Extended Washer Thickness:**

Between 0.168 inches and 0.188 inches

**Grip Diameter:**

Between 0.7480 inches and 0.7490 inches

**End Application:**

C-5 acft

**Thread Diameter:**

0.750 inches

**Grip Length:**

3.125 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Product Name:**

Bolt, shear

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2. Cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.